

# LL4150

## HIGH SPEED SWITCHING DIODE

### FEATURES :


- High switching speed: max. 4 ns
- Continuous reverse voltage: max. 50 V
- For general purpose switching applications
- Pb / RoHS Free

### MECHANICAL DATA :


**Case:** MiniMELF Glass Case (SOD-80)

**Weight:** approx. 0.05g

#### MiniMELF (SOD-80C)



#### Mounting Pad Layout



Dimensions in inches and ( millimeters )

### Maximum Ratings and Thermal Characteristics (Rating at 25 °C ambient temperature unless otherwise specified.)


Parameter	Symbol	Value	Unit
Maximum Reverse Voltage	V <sub>R</sub>	50	V
Forward Continuous Current	I <sub>FM</sub>	300	mA
Maximum Average Forward Current	I <sub>F(AV)</sub>	200	mA
Maximum Power Dissipation	P <sub>D</sub>	500	mW
Maximum Junction Temperature	T <sub>J</sub>	175	°C
Storage Temperature Range	T <sub>S</sub>	-65 to + 175	°C

### Electrical Characteristics (T<sub>J</sub> = 25°C unless otherwise noted)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 50 V	-	-	0.1	µA
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 200 mA	-	-	1.2	V
Reverse Recovery Time	T <sub>rr</sub>	I <sub>F</sub> = 10 mA to 200 mA to I <sub>R</sub> = 10 mA to 200 mA; R <sub>L</sub> = 100 Ω ; measured at I <sub>R</sub> = 0.1x I <sub>F</sub>	-	-	4	ns

## RATING AND CHARACTERISTIC CURVES ( LL4150 )

**FIG. 1 MAXIMUM FORWARD CURRENT  
VERSUS AMBIENT TEMPERATURE**



**FIG. 2 TYPICAL FORWARD VOLTAGE**



**FIG. 3 TYPICAL REVERSE CURRENT  
VERSUS JUNCTION TEMPERATURE**

